## INDEX OF SHEETS

## STATE STANDARDS

SHEET NO.	<u>DESCRIPTION</u>		TANDARD NO. DESCRIPTION	
1	TITLE SHEET		000001-05 TYPICAL SYMBOLS, ABBREVIATIONS AND	PATTERNS
2	INDEX OF SHEETS, STATE STANDARDS & GENERAL NOTES		442201-03 CLASS C AND D PATCHES	
3	SUMMARY OF QUANTITIES		606301-04 PC CONCRETE ISLANDS AND MEDIANS	
4-7	EXISTING AND PROPOSED TYPICAL SECTIONS		701301-03 LANE CLOSURE, 2L, 2W, SHORT TIME OP	ERATIONS
8-10	ROADWAY AND PAVEMENT MARKING PLANS		701306-02 LANE CLOSURE, 2L, 2W, SLOW MOVING OF FOR SPEEDS > 45 MPH	PERATIONS DAY ONLY,
11	DETAILS FOR FRAME AND LIDS ADJUSTMENT WITH MILLING		701311-03 LANE CLOSURE, 2L, WL, MOVING OPERAT	IONS - DAY ONLY
12	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT		701501-05 URBAN LANE CLOSURE, 2L, 2W, UNDIVIDE	ED
13	CURB AND GUTTER REMOVAL AND REPLACEMENT DETAILS		701601-00 URBAN LANE CLOSURE, MULTILANE, 1W O	
14	BUTT JOINT AND HMA TAPER DETAILS		701901-01 TRAFFIC CONTROL DEVICES	
15	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS AND DRIVEWAYS			
16	TYPICAL APPLICATIONS: RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)			
17	DISTRICT ONE TYPICAL PAVEMENT MARKINGS	, inc		and the second s
18	TRAFFIC CONTROL AND PROTECTION OF TURN BAYS (TO REMAIN OPEN TO TRAFFIC)	•		

## GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT (800) 892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE, AND GAS FACILITIES. (48 HOUR NOTIFICATION REQUIRED)

THE CONTRACTOR WILL NOT BE ABLE TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT THE WRITTEN PERMISSION OF THE DEPARTMENT.

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGE OF LIBERTYVILLE.

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT) IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS UNLESS OTHERWISE SPECIFIED.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC, THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1½INCHES WHERE THE SPEED LIMIT IS 45 MPH OR LESS, AND 1 INCH WHERE THE SPEED LIMIT IS OVER 45 MPH. WITH WRITTEN APPROVAL FROM THE RESIDENT ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM OF 1:3 (V:H).

WHEN ARTIFICIAL LIGHTING IS UTILIZED IN NIGHT OPERATIONS. THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISABILITY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.

ALL PAVEMENT PATCHING LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXISTING PAVEMENT MARKING LINES (AND RAISED REFLECTIVE PAVEMENT MARKERS) IN ORDER THAT THESE LOCATIONS CAN BE RE-ESTABLISHED FOR STRIPING. EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY THE ENGINEER.

DOUBLE LANE MARKERS ARE TO BE USED AS SHOWN ON THE DISTRICT ONE DETAIL "TYPICAL APPLICATIONS - RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)" SNOWN IN THE PLANS.

THE RESIDENT ENGINEER SHALL CONTACT DEBBIE HANLON, AREA TRAFFIC FIELD ENGINEER, AT (847) 438-2300 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF FINAL PAVEMENT MARKINGS.

THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO THE INSTALLATION OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.

ı						
	FILE NAME =	USER NAME = whitetar	DESIGNED	- :	REVISED	-
	c:\pw_work\pwidot\whitetar\dØ175544\D125	410-sht-plan.dgn	DRAWN	<u></u> †₩	REVISED	
	•	PLOT SCALE = 50.0000 '/ IN.	CHECKED	**	REVISED	
į		PLOT DATE = 2/4/2010	DATE	-	REVISED	-

PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING

ARTERIAL INFORMATION SIGNING

20

STATE	OF	ILLINOIS
DEPARTMENT	OF	TRANSPORTATION

' I I I I I I I I I I I I I I I I I I I			
ILL 137 (US 45 TO BUTTERFIELD ROAD)	F.A.P. RTE.	SECTION	CO
INDEX OF SHEETS, STATE STANDARDS AND GENERAL NOTES	352	2R-RS-2	L
			CO
SCALE: SHEET NO. OF SHEETS STA. TO STA.		ILLINOIS FED. A	AID PROJ